

B1230N2B | 内转子无槽无传感器 Inner Rotor, Slotless, Sensorless

应用领域：医疗器械、工业设备等精密驱动领域。

Applications: precision drives in medical equipment, industrial automation fields.

主要技术指标 | Characteristics

			28-115-12.0	10-180-9.0	15-180-3.7	
1	电压	Voltage	V	12.0	9.0	3.7
2	端电阻	Terminal resistance	Ω	9	2.4	0.6
3	空载转速	No-load speed	rpm	11500	18000	18000
4	空载电流	No-load current	A	0.05	0.15	0.23
5	堵转转矩	Stall torque	mNm	12.3	16.5	11.2
6	堵转电流	Stall current	A	1.4	3.8	6.2
7	额定转矩	Nominal torque	mNm	3.8	2.7	2.7
8	额定转速	Nominal speed	rpm	6800	14100	12200
9	额定电流	Nominal current	A	0.45	0.74	1.7
10	最大输出功率	Max. output power	W	3.7	7.8	5.9
11	最大效率	Max. efficiency	%	65	64	67
12	反电势常数	Back-EMF constant	mV/rpm	1.0	0.5	0.2
13	转矩常数	Torque constant	mNm/A	9.6	4.6	1.9
14	KV 值	KV Value	rpm/V	960	2000	4860
15	转速 / 转矩斜率	Speed/torque gradient	rpm/mNm	930	1090	1430
16	转子惯量	Rotor inertia	gcm ²	0.21	0.21	0.21
17	重量	Weight	g	15	15	15
18	热阻 (机壳 - 环境)	Thermal resistance housing-ambient	K/W		24	
19	热阻 (线圈 - 机壳)	Thermal resistance winding-housing	K/W		4.5	
20	热时常数 (电机)	Thermal time constant motor	s		240	
21	热时常数 (线圈)	Thermal time constant winding	s		2	
22	工作温度范围	Operating temperature range	°C		-40~+100	
23	绕组耐温等级	Thermal class of winding	°C		155	
24	轴向间隙	Axial play	mm		0.012	
25	径向间隙	Radial play	mm		0.008	
26	动态轴向载荷	Axial load dynamic	N		1	
27	静态轴向载荷	Axial load static	N		25	
28	径向载荷 (距安装面 3mm)	Radial load at 3 mm from mounting face	N		6.3	
29	极对数	No. of pole pairs			1	
30	轴承	Bearings			2 枚滚动轴承/2 ball bearings	
31	换向结构	Commutation			无传感器/Sensorless	
32	防护等级	Protection class			IP 30	

★可选参数 Options: 导线长度 Lead wires length 轴长 Shaft length 性能 Special coils 齿轮箱 Gearheads 轴承类型 Bearing type

编码器 Encoder 驱动器 Driver

外观图 | Outline Drawing

